



## Technical parameters for heat pump space heaters and heat pump combination heaters

As by ANNEX II, point 5 - REQUIREMENTS FOR PRODUCT INFORMATION, Table 2 - COMMISSION REGULATION (EU) No 813/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for space heaters and combination heaters and by ANNEX V - Table 8 of COMMISSION REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device.

Model		AGHPSA061SH / AGHPS061W					
Type of heat pump	<input checked="" type="checkbox"/> Air-to-water heat pump <input type="checkbox"/> Water-to-water heat pump <input type="checkbox"/> Brine-to-water heat pump						
Low-temperature heat pump	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No						
Equipped with a supplementary heater	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Heat pump combination heater	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Climate	<input checked="" type="checkbox"/> Average <input type="checkbox"/> Colder <input type="checkbox"/> Warmer						
Temperature application	<input type="checkbox"/> Medium (55°C) <input checked="" type="checkbox"/> Low (35°C)						
Applied standards	EN14825 / EN16147						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output	Prated	6	kW	Seasonal space heating energy efficiency	$\eta_s$	178,7	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7°C	Pdh	5,30	kW	Tj = - 7°C	COPd	2,81	-
Degradation coefficient	Cdh	0,99	-	Tj = + 2°C	COPd	4,68	-
Tj = + 2°C	Pdh	3,30	kW	Tj = + 7°C	COPd	6,22	-
Degradation coefficient	Cdh	0,96	-	Tj = + 12°C	COPd	5,72	-
Tj = + 7°C	Pdh	2,60	kW	Tj = bivalent temperature	COPd	2,81	-
Degradation coefficient	Cdh	0,94	-	Tj = operation limit temperature	COPd	2,56	-
Tj = + 12°C	Pdh	2,60	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	kW
Degradation coefficient	Cdh	0,94	-	Operation limit temperature	TOL	-10	°C
Tj = bivalent temperature	Pdh	5,30	kW	Cycling interval efficiency	COPcyc	-	-
Tj = operation limit temperature	Pdh	4,20	kW	Heating water operating limit temperature	WTOL	60	°C
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	-7	°C				
Cycling interval capacity for heating	Pcyc	-	kW				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P <sub>OFF</sub>	0,025	kW	Rated heat output	P <sub>sup</sub>	1,8	kW
Thermostat-off mode	P <sub>SB</sub>	0,025	kW	Type of energy input	Electric		
Standby mode	P <sub>TO</sub>	0,025	kW				
Crankcase heater mode	P <sub>CK</sub>	0,025	kW				
Other items							
Capacity control	variable			Rated air flow rate, outdoor	-	3200	m <sup>3</sup> /h
Sound power level, indoor / outdoor	L <sub>WA</sub>	42/62	dB	Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h
Annual energy consumption	Q <sub>HE</sub>	2729	kWh				
For heat pump combination heater							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	107,5	%
Daily electricity consumption	Q <sub>elec</sub>	7532	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual electricity consumption	AEC	1559	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	ARGOCLIMA S.p.A.Via Alfeno Varo, 35, 25020, Alfianello (BS), Italy						



## Technical parameters for heat pump space heaters and heat pump combination heaters

As by ANNEX II, point 5 - REQUIREMENTS FOR PRODUCT INFORMATION, Table 2 - COMMISSION REGULATION (EU) No 813/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for space heaters and combination heaters and by ANNEX V - Table 8 of COMMISSION REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device.

Model		AGHPSA061SH / AGHPS061W					
Type of heat pump	<input checked="" type="checkbox"/> Air-to-water heat pump <input type="checkbox"/> Water-to-water heat pump <input type="checkbox"/> Brine-to-water heat pump						
Low-temperature heat pump	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No						
Equipped with a supplementary heater	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Heat pump combination heater	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Climate	<input type="checkbox"/> Average <input checked="" type="checkbox"/> Colder <input type="checkbox"/> Warmer						
Temperature application	<input type="checkbox"/> Medium (55°C) <input checked="" type="checkbox"/> Low (35°C)						
Applied standards	EN14825 / EN16147						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output	Prated	4	kW	Seasonal space heating energy efficiency	$\eta_s$	144,5	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7°C	Pdh	2,60	kW	Tj = - 7°C	COPd	2,69	-
Degradation coefficient	Cdh	0,97	-	Tj = + 2°C	COPd	5,34	-
Tj = + 2°C	Pdh	2,30	kW	Tj = + 7°C	COPd	7,04	-
Degradation coefficient	Cdh	0,94	-	Tj = + 12°C	COPd	6,90	-
Tj = + 7°C	Pdh	2,70	kW	Tj = bivalent temperature	COPd	1,98	-
Degradation coefficient	Cdh	0,94	-	Tj = operation limit temperature	COPd	1,58	-
Tj = + 12°C	Pdh	2,60	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	1,98	kW
Degradation coefficient	Cdh	0,93	-	Operation limit temperature	TOL	-22	°C
Tj = bivalent temperature	Pdh	3,40	kW	Cycling interval efficiency	COPcyc	-	-
Tj = operation limit temperature	Pdh	2,70	kW	Heating water operating limit temperature	WTOL	60	°C
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	3,40	kW				
Bivalent temperature	Tbiv	-15	°C				
Cycling interval capacity for heating	Pcyc	-	kW				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P <sub>OFF</sub>	0,025	kW	Rated heat output	P <sub>sup</sub>	1,3	kW
Thermostat-off mode	P <sub>SB</sub>	0,025	kW	Type of energy input	Electric		
Standby mode	P <sub>TO</sub>	0,025	kW				
Crankcase heater mode	P <sub>CK</sub>	0,025	kW				
Other items				Rated air flow rate, outdoor			
Capacity control	variable			-	3200	m <sup>3</sup> /h	
Sound power level, indoor / outdoor	L <sub>WA</sub>	42/62	dB	Rated brine or water flow rate, outdoor heat exchanger			
Annual energy consumption	Q <sub>HE</sub>	2674	kWh	-	-	m <sup>3</sup> /h	
For heat pump combination heater							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	79,6	%
Daily electricity consumption	Q <sub>elec</sub>	10033	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual electricity consumption	AEC	2104	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	ARGOCLIMA S.p.A. Via Alfeno Varo, 35, 25020, Alfianello (BS), Italy						



## Technical parameters for heat pump space heaters and heat pump combination heaters

As by ANNEX II, point 5 - REQUIREMENTS FOR PRODUCT INFORMATION, Table 2 - COMMISSION REGULATION (EU) No 813/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for space heaters and combination heaters and by ANNEX V - Table 8 of COMMISSION REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device.

Model		AGHPSA061SH / AGHPS061W					
Type of heat pump	<input checked="" type="checkbox"/> Air-to-water heat pump <input type="checkbox"/> Water-to-water heat pump <input type="checkbox"/> Brine-to-water heat pump						
Low-temperature heat pump	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No						
Equipped with a supplementary heater	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Heat pump combination heater	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Climate	<input type="checkbox"/> Average <input type="checkbox"/> Colder <input checked="" type="checkbox"/> Warmer						
Temperature application	<input type="checkbox"/> Medium (55°C) <input checked="" type="checkbox"/> Low (35°C)						
Applied standards	EN14825 / EN16147						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output	Prated	5	kW	Seasonal space heating energy efficiency	$\eta_s$	232,3	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7°C	Pdh	-	kW	Tj = - 7°C	COPd	-	-
Degradation coefficient	Cdh	-	-	Tj = + 2°C	COPd	3,53	-
Tj = + 2°C	Pdh	5,20	kW	Tj = + 7°C	COPd	5,57	-
Degradation coefficient	Cdh	0,98	-	Tj = + 12°C	COPd	7,60	-
Tj = + 7°C	Pdh	3,30	kW	Tj = bivalent temperature	COPd	3,53	-
Degradation coefficient	Cdh	0,96	-	Tj = operation limit temperature	COPd	3,53	-
Tj = + 12°C	Pdh	2,90	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	kW
Degradation coefficient	Cdh	0,93	-	Operation limit temperature	TOL	2	°C
Tj = bivalent temperature	Pdh	5,20	kW	Cycling interval efficiency	COPcyc	-	-
Tj = operation limit temperature	Pdh	5,20	kW	Heating water operating limit temperature	WTOL	60	°C
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	2	°C				
Cycling interval capacity for heating	Pcyc	-	kW				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P <sub>OFF</sub>	0,025	kW	Rated heat output	P <sub>sup</sub>	0,0	kW
Thermostat-off mode	P <sub>SB</sub>	0,025	kW	Type of energy input	Electric		
Standby mode	P <sub>TO</sub>	0,025	kW				
Crankcase heater mode	P <sub>CK</sub>	0,025	kW				
Other items				Rated air flow rate, outdoor			
Capacity control	variable			-	3200	m <sup>3</sup> /h	
Sound power level, indoor / outdoor	L <sub>WA</sub>	42/62	dB	Rated brine or water flow rate, outdoor heat exchanger			
Annual energy consumption	Q <sub>HE</sub>	1136	kWh	-	-	m <sup>3</sup> /h	
For heat pump combination heater							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	111	%
Daily electricity consumption	Q <sub>elec</sub>	7282	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual electricity consumption	AEC	1509	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	ARGOCLIMA S.p.A. Via Alfeno Varo, 35, 25020, Alfianello (BS), Italy						



## Technical parameters for heat pump space heaters and heat pump combination heaters

As by ANNEX II, point 5 - REQUIREMENTS FOR PRODUCT INFORMATION, Table 2 - COMMISSION REGULATION (EU) No 813/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for space heaters and combination heaters and by ANNEX V - Table 8 of COMMISSION REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device.

Model		AGHPSA061SH / AGHPS061W					
Type of heat pump	<input checked="" type="checkbox"/> Air-to-water heat pump <input type="checkbox"/> Water-to-water heat pump <input type="checkbox"/> Brine-to-water heat pump						
Low-temperature heat pump	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No						
Equipped with a supplementary heater	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Heat pump combination heater	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Climate	<input checked="" type="checkbox"/> Average <input type="checkbox"/> Colder <input type="checkbox"/> Warmer						
Temperature application	<input checked="" type="checkbox"/> Medium (55°C) <input type="checkbox"/> Low (35°C)						
Applied standards	EN14825 / EN16147						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output	Prated	5	kW	Seasonal space heating energy efficiency	$\eta_s$	127,4	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7°C	Pdh	4,00	kW	Tj = - 7°C	COPd	2,03	-
Degradation coefficient	Cdh	0,99	-	Tj = + 2°C	COPd	3,27	-
Tj = + 2°C	Pdh	2,60	kW	Tj = + 7°C	COPd	4,20	-
Degradation coefficient	Cdh	0,97	-	Tj = + 12°C	COPd	6,00	-
Tj = + 7°C	Pdh	2,40	kW	Tj = bivalent temperature	COPd	2,03	-
Degradation coefficient	Cdh	0,96	-	Tj = operation limit temperature	COPd	1,38	-
Tj = + 12°C	Pdh	2,80	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	kW
Degradation coefficient	Cdh	0,95	-	Operation limit temperature	TOL	-10	°C
Tj = bivalent temperature	Pdh	4,00	kW	Cycling interval efficiency	COPcyc	-	-
Tj = operation limit temperature	Pdh	3,80	kW	Heating water operating limit temperature	WTOL	60	°C
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	-7	°C				
Cycling interval capacity for heating	Pcyc	-	kW				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P <sub>OFF</sub>	0,025	kW	Rated heat output	P <sub>sup</sub>	1,2	kW
Thermostat-off mode	P <sub>SB</sub>	0,025	kW	Type of energy input	Electric		
Standby mode	P <sub>TO</sub>	0,025	kW				
Crankcase heater mode	P <sub>CK</sub>	0,025	kW				
Other items				Rated air flow rate, outdoor			
Capacity control	variable			-	3200	m <sup>3</sup> /h	
Sound power level, indoor / outdoor	L <sub>WA</sub>	42/62	dB	Rated brine or water flow rate, outdoor heat exchanger			
Annual energy consumption	Q <sub>HE</sub>	3169	kWh	-	-	m <sup>3</sup> /h	
For heat pump combination heater							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	107,5	%
Daily electricity consumption	Q <sub>elec</sub>	7532	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual electricity consumption	AEC	1559	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	ARGOCLIMA S.p.A.Via Alfeno Varo, 35, 25020, Alfianello (BS), Italy						



## Technical parameters for heat pump space heaters and heat pump combination heaters

As by ANNEX II, point 5 - REQUIREMENTS FOR PRODUCT INFORMATION, Table 2 - COMMISSION REGULATION (EU) No 813/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for space heaters and combination heaters and by ANNEX V - Table 8 of COMMISSION REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device.

Model		AGHPSA061SH / AGHPS061W					
Type of heat pump	<input checked="" type="checkbox"/> Air-to-water heat pump <input type="checkbox"/> Water-to-water heat pump <input type="checkbox"/> Brine-to-water heat pump						
Low-temperature heat pump	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No						
Equipped with a supplementary heater	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Heat pump combination heater	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Climate	<input type="checkbox"/> Average <input checked="" type="checkbox"/> Colder <input type="checkbox"/> Warmer						
Temperature application	<input checked="" type="checkbox"/> Medium (55°C) <input type="checkbox"/> Low (35°C)						
Applied standards	EN14825 / EN16147						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output	Prated	4	kW	Seasonal space heating energy efficiency	$\eta_s$	103,6	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7°C	Pdh	2,40	kW	Tj = - 7°C	COPd	1,83	-
Degradation coefficient	Cdh	0,98	-	Tj = + 2°C	COPd	3,87	-
Tj = + 2°C	Pdh	2,10	kW	Tj = + 7°C	COPd	5,31	-
Degradation coefficient	Cdh	0,95	-	Tj = + 12°C	COPd	6,73	-
Tj = + 7°C	Pdh	2,50	kW	Tj = bivalent temperature	COPd	1,38	-
Degradation coefficient	Cdh	0,95	-	Tj = operation limit temperature	COPd	1,10	-
Tj = + 12°C	Pdh	2,90	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	1,38	kW
Degradation coefficient	Cdh	0,94	-	Operation limit temperature	TOL	-22	°C
Tj = bivalent temperature	Pdh	3,10	kW	Cycling interval efficiency	COPcyc	-	-
Tj = operation limit temperature	Pdh	2,30	kW	Heating water operating limit temperature	WTOL	60	°C
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	3,10	kW				
Bivalent temperature	Tbiv	-15	°C				
Cycling interval capacity for heating	Pcyc	-	kW				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P <sub>OFF</sub>	0,025	kW	Rated heat output	P <sub>sup</sub>	1,7	kW
Thermostat-off mode	P <sub>SB</sub>	0,025	kW	Type of energy input	Electric		
Standby mode	P <sub>TO</sub>	0,025	kW				
Crankcase heater mode	P <sub>CK</sub>	0,025	kW				
Other items				Rated air flow rate, outdoor			
Capacity control	variable			-	3200	m <sup>3</sup> /h	
Sound power level, indoor / outdoor	L <sub>WA</sub>	42/62	dB	Rated brine or water flow rate, outdoor heat exchanger			
Annual energy consumption	Q <sub>HE</sub>	3701	kWh	-	-	m <sup>3</sup> /h	
For heat pump combination heater							
Declared load profile	XL			Water heating energy efficiency	$\eta_{wh}$	79,6	%
Daily electricity consumption	Q <sub>elec</sub>	10033	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual electricity consumption	AEC	2104	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	ARGOCLIMA S.p.A.Via Alfeno Varo, 35, 25020, Alfianello (BS), Italy						



## Technical parameters for heat pump space heaters and heat pump combination heaters

As by ANNEX II, point 5 - REQUIREMENTS FOR PRODUCT INFORMATION, Table 2 - COMMISSION REGULATION (EU) No 813/2013 of 2 August 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for space heaters and combination heaters and by ANNEX V - Table 8 of COMMISSION REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device.

Model		AGHPSA061SH / AGHPS061W					
Type of heat pump	<input checked="" type="checkbox"/> Air-to-water heat pump <input type="checkbox"/> Water-to-water heat pump <input type="checkbox"/> Brine-to-water heat pump						
Low-temperature heat pump	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No						
Equipped with a supplementary heater	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Heat pump combination heater	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No						
Climate	<input type="checkbox"/> Average <input type="checkbox"/> Colder <input checked="" type="checkbox"/> Warmer						
Temperature application	<input checked="" type="checkbox"/> Medium (55°C) <input type="checkbox"/> Low (35°C)						
Applied standards	EN14825 / EN16147						
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output	Prated	5	kW	Seasonal space heating energy efficiency	$\eta_s$	166,7	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7°C	Pdh	-	kW	Tj = - 7°C	COPd	-	-
Degradation coefficient	Cdh	-	-	Tj = + 2°C	COPd	3,52	-
Tj = + 2°C	Pdh	5,20	kW	Tj = + 7°C	COPd	3,49	-
Degradation coefficient	Cdh	0,98	-	Tj = + 12°C	COPd	5,67	-
Tj = + 7°C	Pdh	3,30	kW	Tj = bivalent temperature	COPd	3,52	-
Degradation coefficient	Cdh	0,97	-	Tj = operation limit temperature	COPd	3,52	-
Tj = + 12°C	Pdh	2,70	kW	Tj = - 15 °C (if TOL < - 20 °C)	COPd	-	kW
Degradation coefficient	Cdh	0,95	-	Operation limit temperature	TOL	2	°C
Tj = bivalent temperature	Pdh	5,20	kW	Cycling interval efficiency	COPcyc	-	-
Tj = operation limit temperature	Pdh	5,20	kW	Heating water operating limit temperature	WTOL	60	°C
Tj = - 15 °C (if TOL < - 20 °C)	Pdh	-	kW				
Bivalent temperature	Tbiv	2	°C				
Cycling interval capacity for heating	Pcyc	-	kW				
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P <sub>OFF</sub>	0,025	kW	Rated heat output	P <sub>sup</sub>	0,0	kW
Thermostat-off mode	P <sub>SB</sub>	0,025	kW	Type of energy input	Electric		
Standby mode	P <sub>TO</sub>	0,025	kW				
Crankcase heater mode	P <sub>CK</sub>	0,025	kW				
Other items				Rated air flow rate, outdoor			
Capacity control	variable				-	3200	m <sup>3</sup> /h
Sound power level, indoor / outdoor	L <sub>WA</sub>	42/62	dB	Rated brine or water flow rate, outdoor heat exchanger	-	-	m <sup>3</sup> /h
Annual energy consumption	Q <sub>HE</sub>	1575	kWh				
For heat pump combination heater				Water heating energy efficiency			
Declared load profile	XL				$\eta_{wh}$	111	%
Daily electricity consumption	Q <sub>elec</sub>	7282	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh
Annual electricity consumption	AEC	1509	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	ARGOCLIMA S.p.A.Via Alfeno Varo, 35, 25020, Alfianello (BS), Italy						



## PRODUCT FICHE

As by ANNEX IV - POINT 1 of COMMISSION REGULATION (EU) No 811/2013 of 18 February 2013 supplementing Directive 2010/30/EU of the European Parliament and of the Council with regard to the energy labelling of space heaters, combination heaters, packages of space heater, temperature control and solar device and packages of combination heater, temperature control and solar device.

### MEDIUM TEMPERATURE HEAT PUMP - Low & Medium temperature application

MODEL : AGHPSA061SH / AGHPS061W

SEASONAL SPACE HEATING ENERGY EFFICIENCY CLASS			<b>A++</b>
		55°C	
Rated heat output (average climate conditions)	Prated	5	kW
DECLARED LOAD PROFILE			<b>XL</b>
SEASONAL WATER HEATING ENERGY EFFICIENCY CLASS			<b>A</b>
		55°C	
Annual energy consumption (average climate conditions)	Q <sub>HE</sub>	3169	kWh
Annual electricity consumption for water heating (average climate conditions)	AEC	1559	kWh
		55°C	
Seasonal space heating energy efficiency (average climate conditions)	η <sub>s</sub>	127	%
Water heating energy efficiency (average climate conditions)	η <sub>wh</sub>	107,5	%
		55°C	
Rated heat output (colder climate conditions)	P <sub>nominale</sub>	4	kW
Rated heat output (warmer climate conditions)	P <sub>nominale</sub>	5	kW
		55°C	
Annual electricity consumption for space heating (colder climate conditions)	Q <sub>HE</sub>	3701	kWh
Annual electricity consumption for space heating (warmer climate conditions)	Q <sub>HE</sub>	1575	kWh
Annual electricity consumption for water heating (colder climate conditions)	AEC	2104	kWh
Annual electricity consumption for water heating (warmer climate conditions)	AEC	1509	kWh
		55°C	
Seasonal space heating energy efficiency (colder climate conditions)	η <sub>s</sub>	103,6	%
Seasonal space heating energy efficiency (warmer climate conditions)	η <sub>s</sub>	166,7	%
Water heating energy efficiency (colder climate conditions)	η <sub>wh</sub>	79,6	%
Water heating energy efficiency (warmer climate conditions)	η <sub>wh</sub>	111	%
		Outdoor	
Sound power level	L <sub>WA</sub>	62	dB
Contact information	<b>Argoclima Spa - Via Alfeno Varo 35 - 25020 Alfianello (BS) ITALY</b>		

**Specific precautions for assembly, installation and maintenance of the combined heat pump:**

- (1) Before proceeding with the installation, check that the power supply used corresponds to that indicated on the data plate and check the safety of the current;
- (2) Before use, check and confirm that the electrical connections and water pipes are made correctly, to avoid water leaks, electric shocks or fires;
- (3) Do not operate the machine with wet hands and do not allow children to play with the unit;
- (4) The On / Off key is used to switch the unit on or off by the end user, to switch off the unit completely disconnect the power cord;
- (5) Do not expose the unit to corrosive environment with water or humidity;
- (6) Do not use the unit without water in the tank. The air delivery and return must not be obstructed with objects;
- (7) The water in the unit and piping should be drained when not using the unit to prevent freeze breakage of the tank, water pipes and water pump;
- (8) Never press the button with sharp objects to avoid damaging the hand control.  
Never use other connections instead of the special communication lines of the unit to protect the control elements.  
Never clean the hand control with benzine or thinner to avoid discoloration of the surface or elements being damaged.  
Clean the unit with a damp cloth. Gently clean the display screen and connecting parts to prevent them from being damaged;
- (9) The power cable must be separated from the communication lines.