



INFORMATION SHEET FOR AIR CONDITIONERS, EXCEPT DOUBLE DUCTS AND SINGLE DUCTS⁽⁵⁾

As by Commission Communication in the framework of ecodesign requirements for air conditioners and comfort fans (EU Regulation no. 206/2012) and of energy labelling of air conditioners - (EU Regulation no. 626/2011)

MODEL : X3I PLUS EVO 71 SH LH/ X3I PLUS EVO 71 HL WF LH

Function to which information applies				If information applies to heating: heating season to which information relates.			
Cooling		Y		Heating (Average)(-10°C)			Y
Heating		Y		Heating (Warmer)(+2°C)			Y
				Heating (Colder)(-22°C)			Y
Item	symbol	Valore	unit	Item	symbol	Valore	unit
Design load				Seasonal efficiency			
Cooling	Pdesignc	7,1	kW	Cooling	SEER	7,0	-
Heating (Average)(-10°C)	Pdesignh	5,6	kW	Heating (Average)(-10°C)	SCOP (A)	4,2	-
Heating (Warmer)(+2°C)	Pdesignh	5,7	kW	Heating (Warmer)(+2°C)	SCOP (W)	5,4	-
Heating (Colder)(-22°C)	Pdesignh	6,3	kW	Heating (Colder)(-22°C)	SCOP (C)	3,4	-
Declared capacity (*) for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj				Declared Energy efficiency ratio (*) for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj = 35°C	Pdc	7,11	kW	Tj = 35°C	EERd	3,58	-
Tj = 30°C	Pdc	5,18	kW	Tj = 30°C	EERd	5,29	-
Tj = 25°C	Pdc	3,33	kW	Tj = 25°C	EERd	8,46	-
Tj = 20°C	Pdc	2,86	kW	Tj = 20°C	EERd	12,52	-
Declared capacity (*) for heating / Average season, at indoor temperature 20°C and outdoor temperature Tj				Declared Coefficient of Performance (*) for heating / Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	4,82	kW	Tj = -7°C	COPd	2,85	-
Tj = 2°C	Pdh	2,92	kW	Tj = 2°C	COPd	4,07	-
Tj = 7°C	Pdh	1,98	kW	Tj = 7°C	COPd	5,53	-
Tj = 12°C	Pdh	2,45	kW	Tj = 12°C	COPd	6,81	-
Tj = bivalent temperature	Pdh	5,66	kW	Tj = bivalent temperature	COPd	2,01	-
Tj = operating limit temperature	Pdh	5,66	kW	Tj = operating limit temperature	COPd	2,01	-
Declared capacity (*) for heating / Warmer season, at indoor temperature 20°C and outdoor temperature Tj				Declared Coefficient of Performance (*) for heating / Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj = 2°C	Pdh	5,71	kW	Tj = 2°C	COPd	2,69	-
Tj = 7°C	Pdh	3,60	kW	Tj = 7°C	COPd	5,25	-
Tj = 12°C	Pdh	2,45	kW	Tj = 12°C	COPd	6,81	-
Tj = bivalent temperature	Pdh	5,71	kW	Tj = bivalent temperature	COPd	2,69	-
Tj = operating limit temperature	Pdh	5,71	kW	Tj = operating limit temperature	COPd	2,69	-
Declared capacity (*) for heating / Colder season, at indoor temperature 20°C and outdoor temperature Tj				Declared Coefficient of Performance (*) for heating / Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj = -7°C	Pdh	3,73	kW	Tj = -7°C	COPd	2,93	-
Tj = 2°C	Pdh	2,25	kW	Tj = 2°C	COPd	4,13	-
Tj = 7°C	Pdh	1,98	kW	Tj = 7°C	COPd	5,53	-
Tj = 12°C	Pdh	2,45	kW	Tj = 12°C	COPd	6,81	-
Tj = bivalent temperature	Pdh	4,82	kW	Tj = bivalent temperature	COPd	1,82	-
Tj = operating limit temperature	Pdh	5,20	kW	Tj = operating limit temperature	COPd	1,86	-
Tj = -15°C	Pdh	-	kW	Tj = -15°C	COPd	-	-
Bivalent temperature				Operating limit temperature			
Heating (Average)	Tbiv	-10	°C	Heating (Average)	Tol	-10	°C
Heating (Warmer)	Tbiv	2	°C	Heating (Warmer)	Tol	2	°C
Heating (Colder)	Tbiv	-15	°C	Heating (Colder)	Tol	-20	°C
Power consumption of cycling				Efficiency of cycling			
Cooling	Pcyc	nd	kW	Cooling	EERcyc	nd	-
Heating	Pcyc	nd	kW	Heating	COPcyc	nd	-
Degradation coefficient cooling(**)	Cdc	0,25	-	Degradation coefficient heating(**)	Cdh	0,25	-
Electric power input in power modes other than "active mode"				Seasonal electricity consumption			
Off mode	P _{OFF}	0,00509	kW	Cooling	Q _{CE}	355	kWh/a
Standby mode	P _{SB}	0,00509	kW	Heating (Average)(-10°C)	Q _{HE/A}	1867	kWh/a
Thermostat-off mode	P _{TO}	0,00211/0,01388	kW	Heating (Warmer)(+2°C)	Q _{HE/W}	1478	kWh/a
Crankcase heater mode	P _{CK}	0	kW	Heating (Colder)(-22°C)	Q _{HE/C}	3891	kWh/a
Capacity control type				Other items			
Fixed		N		Sound power level (indoor/outdoor)	L _{WA}	64/70	dB(A)
Staged		N		Refrigerant type		R32	
Variable		Y		Global warming potential	GWP	675	KgCO ₂ eq.
				Rated air flow (indoor/outdoor)		1250/3600	m ³ /h
For more detailed information				ARGOCLIMA SPA - Via A. Varo,35 - Alfianello (BS) - ITALY - www.argoclima.com			

(5) For multisplit appliances, data shall be provided at a Capacity ratio of 1.

(**) If default Cd= 0,25 is chosen, then results from cycling tests are not required. Otherwise either the heating or cooling cycling test value is required



Product Fiche

Model: X3I PLUS EVO 71 SH LH / X3I PLUS EVO 71 HL WF

Manufacturer : ARGOCLIMA SPA - via Alfeno Varo, 35 - Alfianello (BS) - Italy;

Sound power level (indoor unit / outdoor unit): 64/70 dB(A);

Refrigerant: R32

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling mode

SEER: 7,0

Energy efficiency class: A++

Pdesignc: 7,1 kW

Annual electricity consumption 355 kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

Heating mode

Climate type: Warmer / Average / Colder

SCOP: 5,4 / 4,2 / 3,4

Energy efficiency class: A+++/A+/A

Pdesignh: 5,7 / 5,6 / 6,3 Kw

Declared capacity: 5,7 / 5,6 / 0 kW

The back up heating capacity for SCOP calculation: **0 / 0 / 6,3 kW.**

Annual electricity consumption **1478/1867/3891** kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.